

SAV0812 PVC SELF-ADHESIVE VINYL

Description

Soft white Monomeric PVC film

Color: Transparent.

Surface: Glossy

Release paper

120g±10gsm PEK release paper

Adhesive

Solvent polyacrylate, Permanent, Transparent

Technical datas

Thickness (without protective paper and adhesive)	80 micron Monomeric PVC film
Dimensional stability (FINAT TM14)	Adhered to steel, No shrinkage in cross direction, in length 0.50mm max
Temperature resistance	Adhered to aluminum. -20°C to +65°C, no variation.
Adhesive	Solvent polyacrylate Permanent Transparent adhesive
Seawater resistance (DIN 50021)	Adhered to aluminum, after 48h/23°C no variation.
Adhesive power (FINAT TM 1, initial, stainless steel)	8-10N / 25MM
Adhesive power (FINAT TM 1,ultimate, stainless steel)	12-14N/25MM
Shelf life	1 year stroed at 22° C/50-55 % RH
Application temperature	min. +10°C
Standard length	50M / 100M / 250M
Width	2.02m/1.82m/1.52m/1.37m/1.27m/1.07m/1.06m/0.914m
Attention: After printing the ink must be thoroughly dry in order to avoid any affect on the later combination with the laminate. Surfaces to which the material will be applied must be thoroughly cleaned from dust, grease or any contamination which could affect the adhesion of the material. The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.	