

TITAN DOME | TDW-100

High tack satin white print vinyl developed for applying smaller graphics on helmets or other curved surfaces.

FACE FILM

Polymeric PVC, satin white

Thickness (µm)	100	
Elongation at break (%)	>200	DIN EN ISO 527

ADHESIVE

Clear solvent-based acrylic, high tack permanent

Thickness (µm)	30	
Adhesion to steel		FINAT FTM 1
20 minutes (180°) N/25mm	22	
24 hours (180°) N/25mm	28	

RELEASE LINER

Lay-flat kraft paper liner, double-sided PE-coated

Weight (gsm)	140
--------------	-----

PRODUCT APPLICATION

Application method	Dry
Application temperature (°C)	10 to 30
Service temperature (°C)	-20 to 70

DURABILITY

Shelf life (months)	12	
Outdoor durability (years)	8	Northern-EU climate, vertical exposure

ROLL SIZES

1370mm x 50m

PRINTING METHOD

(Eco)-Solvent, Latex, UV

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in TITAN material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.